

THE KEY TO SYMBOLS

KEY

	TILE 1ST BRICK 1ST PYREBAR 1ST	Fire proof construction. (OR FIRE RESISTIVE CONST'N)		MANSARD ROOF DOTS REPRESENT OPENINGS. STEMS INDICATE STORIES, COUNTING FROM LEFT TO RIGHT, LOOKING TOWARD BUILDING.	Window opening in first story. Window openings in second and third stories. Window openings in second and fourth stories. Windows with wired glass. Windows with iron or tin clad shutters. Window openings tenth to twenty-second stories.
	ADDBE	Adobe building.		[E] Open elevator. [FE] Frame enclosed elevator.	
	HEIGHT OF BUILDING IN FEET FROM GROUND TO ROOF LINE.	Stone building.		[ET] " " " with traps. [ESC] " " " self closing traps.	
	(C. BR.)	Concrete, lime, cinder or cement brick		[CBET] Concrete block enclosed elevator with traps.	
	(C. B.)	Hollow concrete or cement block const'n		[TEC] Tile enclosed elevator with self closing traps.	
	(CONC.)	Concrete or reinforced concrete const'n		[BE] Brick enclosed elev. with wired glass door.	
	(TILE)	Tile building.			
	NUMBER OF STORIES 4	Brick building with frame cornice.			
	TWO STORIES AND ASMT 28 COMPOSITION ROOF	" " " stone front. " " " frame side. (DIVIDED BY FRAME PARTITION)			
	SHINGLE ROOF	Brick veneered building			
	(VEND)	" and frame building.			
	BRICK 1ST	Frame building, brick lined.			
	FRAME, BRICK LINED	" " metal clad.			
	F=FLAT S=STORE	Frame building.			
	D=DWELLING	Iron building.			
	A in B AUTO. IN B SWT	Tenant building occupied by various manufacturing or occupancies			
	LOFT	Frame building covered with asbestos			
	(ASB. CL.)	Brick building with brick or metal cornice.			
	NON COMBUSTIBLE ROOF COVERING OF METAL, SLATE, TILE OR ASBESTOS SHINGLES	Fire wall 6 inches above roof.			
	SKYLIGHT LIGHTING TOP STORY ONLY	" " " 12 " " "			
	SKYLIGHT LIGHTING THREE STORIES	" " " 18 " " "			
	WIRED GLASS SKYLIGHT	" " " 36 " " "			
	FIRE WALL 48 INCHES ABOVE ROOF	Figures 8, 12, 16 indicate thickness of wall in inches.			
	2345	Wall without opening and size in inches.			
	ALL	Wall with openings on floors as designated.			
	WATER TANK	Opening with single iron or tin clad door.			
	BRICK 1ST	" " double iron " " " doors.			
	A	" " standard fire doors.			
	(C. B.)	Openings with wired glass doors.			
	(C. B. & BR.)	Drive or passage way.			
	(C. B. & BR. CONST'N)	Stable.			
	(C. B. & BR. CONST'N) (BR. FACED)	Auto. House or private garage.			
	(C. B. & BR. CONST'N)	Solid brick with interior walls of C.B. or C.B. and brick mixed.			
	(C. B. & BR. CONST'N)	Mixed construction of C.B. and brick with one wall of solid brick.			
	(C. B. & BR. CONST'N)	Mixed construction of C.B. and brick with one wall faced with 4" brick.			
	(C. B. & BR. CONST'N)	Mixed construction of C.B. and brick throughout.			
	5	Block number.			
	AFA	Automatic fire alarm.			
	IEP	Independent electric plant.			
	AS	Automatic sprinklers.			
	ACS	Automatic chemical sprinklers.			
	AS (NOTE UNDER SYMBOL INDICATES PROTECTED PORTION OF BUILDING)	Automatic sprinklers in part of building only.			
	NS	Not sprinklered.			
	24	Reference to adjoining page.			
	FA	Fire alarm box.			
	24	Fire engine house, as shown on key map.			
	24	Fire pump.			
	24	Under page number refers to corresponding page of previous edition.			
	D.H.	Single hydrant.			
	24	Double " (36) refers to corresponding page of previous edition.			
	T.H.	Triple "			
	Q.H.	Quadruple hydrant of the "High Pressure Fire Service."			
	H.P.F.S.	Fire alarm box of the "High Pressure Fire Service"			
	H.P.F.S.	Water pipes of the "High Pressure Fire Service"			
	H.P.F.S.	Water pipes of size in inches.			
	H.P.F.S.	Water pipes of private supply			
	H.P.F.S.	House numbers shown nearest to buildings are official or actually up on buildings.			
	H.P.F.S.	Old house numbers shown furthest from buildings.			